




Category: Power Generators

Cummins 4BTAA3.9-G3 C70D5P 70 kVA Power Generator

Ratings & Electrical

- Prime Power: 56 kW / 70 kVA
- Standby Power: ~62 kW / 77 kVA
- Frequency: 50 Hz
- Speed: 1500 rpm
- Voltage: 400/230 V (3-phase)
- Power Factor: 0.8 (lagging)
- Alternator Insulation: Class H
- Voltage Regulation: $\pm 1\%$

Engine / Mechanical

- Engine Model: Cummins 4BTAA3.9-G3
- Configuration: 4-stroke, 4-cylinder, inline, turbocharged & aftercooled
- Displacement: 3.9 L
- Bore × Stroke: 102 mm × 120 mm
- Compression Ratio: 17.2 : 1
- Lubricating Oil Capacity: ~8 L
- Coolant Capacity: ~15 L

Fuel & Consumption

- Fuel Type: Diesel
- Fuel Consumption @100% Load: ~17 L/h
- Fuel Consumption @75% Load: ~13 L/h
- Fuel Tank Capacity: ~200 L (typical enclosure)

Cooling, Exhaust & Air

- Exhaust Gas Temperature: ~460 °C
- Exhaust Gas Flow: ~10 m³/min
- Max Exhaust Back Pressure: 10 kPa
- Cooling System: Radiator-cooled, tropical rating

Physical Dimensions & Weight

- Dimensions (L × W × H): ~2200 mm × 1000 mm × 1400 mm
- Weight (approx.): ~1050 kg (open set)

Alternator & Control

- Alternator Frame: Stamford or equivalent, Class H insulation
- Control Panel: Cummins/DeepSea electronic controller
- Features: Monitoring, protection & optional auto-start/stop